



DETECTOR

GA-72Cd

Applications

Handheld Handheld Types Metal detectors (MD)

Last update 01/01/1970

General description

The GA-72Cd Locator detects the magnetic field of iron and steel objects. It provides audio detection signals that peak in frequency when the locator's tip is held directly over the target. The GA-72Cd has the option of nulling or peaking. Designed for one-hand operations, the On/Off-Sensitivity and Volume controls are located on the underside of the cover. This provides easy access, protects the knobs and contributes to their overall ruggedness and dependability.

Working characteristics

Analog output for data logger entry Modular construction; high performance components Lightweight, easy-to-use-design reduces search time Audio & Visual Output Choice of Two Audio Modes: Peak or Null response Battery & Sensitivity Indicators Signal Strength and Polarity Indications HeliFlux® sensors No response to aluminum, brass, or copper One Year Warranty for UXO use

Radio, audio, visual, sensitivity data

Audio output	Switch at "A" Signal increases or decreases in volume with gradient-field intensity. Switch at "B" Signal increases or decreases in frequency with gradient-field intensity.
Visual display	Digital readout and expanding bar graphs indicate polarity (+ or-) and relative strength of the magnetic field.
Sensitive adjustment	1

Power supply data

Battery	Supplied by two Alkaline or Lithium 9V batteries; Rechargeable batteries are optional
Low battery alert	1
Low battery alert information	4-segment LCD BATT indicator
Operating time information	40 Hours (intermittent usage)
Battery charger provided	1
Battery charger information	Rechargeable Batteries are optional

Dimensional data

Length	870 mm
Weight	1.14 kg
Search head size	32 mm
Shape	Stick
Transport case provided	1
Transport case information	Hard Case Included
Transport case weight	0.9 kg
Transport case weight info	82 cm x 13 cm x 16 cm

Factory support data

Factory support	Our customer support department is committed to providing prompt response and 100% satisfaction. Most Schonstedt locators returned to the factory for a paid repair will be completely refurbished. Not only will it look like new, it will operate within i
Warranty	1 Year Warranty for EOD and UXO Use
Temperature limitations	Operating Temps: -25° to 60°C

Price

Base price	1041 €
Reduction for higher quantity	Call 888-367-7014 or email schonstedt.orders@spx.com for additional pricing

Other

Detectors systems in use to date	GA-52Cx; GA-72Cd-ML;
Other models	GA-52Cx; GA-72Cd-ML;

Other information

Images







